

MR Precision Balances

Robust and Reliable



Designed for Convenience

Advanced technologies, including automatic adjustment and guided leveling, simplify daily weighing. Solidly built and with IP43, cleaning is easy too.



Easy Integration

Multiple interfaces and MT-SICS commands make it simple to connect your MR balance to PLC and MES systems as well as other lab instruments.



User Management

By setting up different user groups and profiles, operators see just the functions and applications they need to carry out their tasks, simplifying processes and reducing errors.



IP43 Protection

IP43 ingress protection prevents dirt and liquid spills from entering the balance, protecting the load cell and electronics. The robust design makes this balance suitable for use in more challenging weighing environments.



Your Weighing Partner

For All Environments

These reliable balances deliver consistently accurate results even in the toughest weighing environments. Built-in applications and multiple connectivity options make these durable balances highly versatile whether you're in the lab or out on the factory floor.

The full metal housing and durable components are tested in the harshest environments to ensure protection against dirt and chemicals. The overload protection safeguards the weighing cell against excess loads and accidental drops on the weighing pan.

When you don't need to use your balance, the configurable power-saving mode minimizes energy usage and saves costs.

METTLER **TOLEDO**

Technical Specifications



	MR203	MR303	MR503	MR603
Limit values				
Capacity	220 g	320 g	520 g	620 g
Readability	1 mg	1 mg	1 mg	1 mg
Repeatability (at 5% load)	1 mg	1 mg	1 mg	1 mg
Linearity deviation	2 mg	2 mg	2 mg	2 mg
Sensitivity offset (at nominal load) ▲	8 mg	8 mg	8 mg	8 mg
Typical values				
Repeatability (at 5% load)	0.7 mg	0.7 mg	0.7 mg	0.7 mg
Linearity deviation	0.6 mg	0.6 mg	0.6 mg	0.6 mg
Sensitivity offset (at nominal load) ▲	5 mg	5 mg	5 mg	5 mg
Minimum weight (USP, tolerance = 0.10%) ▼	1.4 g	1.4 g	1.4 g	1.4 g
Minimum weight (tolerance = 1%) ▼	140 mg	140 mg	140 mg	140 mg
Settling time	1.5 s	1.5 s	1.5 s	1.5 s
Dimensions and other specifications				
Balance dimensions (W × D × H)	209 × 351 × 354 mm			
Weighing pan diameter	120 mm	120 mm	120 mm	120 mm

▲ after adjustment with internal weight

▼ determined at 5% load, k = 2

All models are available as approved versions.



	MR1002	MR2002	MR3002
Limit values			
Capacity	1.2 kg	2.2 kg	3.2 kg
Readability	0.01 g	0.01 g	0.01 g
Repeatability (at 5% load)	10 mg	10 mg	10 mg
Linearity deviation	20 mg	20 mg	20 mg
Sensitivity offset (at nominal load) ▲	60 mg	80 mg	80 mg
Typical values			
Repeatability (at 5% load)	7 mg	7 mg	7 mg
Linearity deviation	6 mg	6 mg	6 mg
Sensitivity offset (at nominal load) ▲	40 mg	50 mg	50 mg
Minimum weight (USP, tolerance = 0.10%) ▼	14 g	14 g	14 g
Minimum weight (tolerance = 1%) ▼	1.4 g	1.4 g	1.4 g
Settling time	1 s	1 s	1 s
Dimensions and other specifications			
Balance dimensions (W × D × H)	209 × 351 × 100 mm	209 × 351 × 100 mm	209 × 351 × 100 mm
Weighing pan dimensions (W × D)	180 × 180 mm	180 × 180 mm	180 × 180 mm

▲ after adjustment with internal weight

▼ determined at 5% load, k = 2

All models are available as approved versions.



	MR4002	MR6002	MR6001
Limit values			
Capacity	4.2 kg	6.2 kg	6.2 kg
Readability	0.01 g	0.01 g	0.1 g
Repeatability (at 5% load)	10 mg	10 mg	80 mg
Linearity deviation	20 mg	20 mg	60 mg
Sensitivity offset (at nominal load) ▲	80 mg	80 mg	300 mg
Typical values			
Repeatability (at 5% load)	7 mg	7 mg	50 mg
Linearity deviation	6 mg	6 mg	20 mg
Sensitivity offset (at nominal load) ▲	50 mg	50 mg	150 mg
Minimum weight (USP, tolerance = 0.10%) ▼	14 g	14 g	100 g
Minimum weight (tolerance = 1%) ▼	1.4 g	1.4 g	10 g
Settling time	1 s	1 s	1 s
Dimensions and other specifications			
Balance dimensions (W × D × H)	209 × 351 × 100 mm	209 × 351 × 100 mm	209 × 351 × 100 mm
Weighing pan dimensions (W × D)	180 × 180 mm	180 × 180 mm	180 × 180 mm

▲ after adjustment with internal weight

▼ determined at 5% load, k = 2

All models are available as approved versions.

Features

Performance

- Electromagnetic Force Compensation (EMFC) weighing cell
- FACT automatic internal adjustment

Efficient Operation

- 4.5" touchscreen
- 9 built-in applications
- Statistical data analysis

Quality Assurance

- OIML/NTEP approved
- User management
- Leveling assistant
- Configurable sample and task IDs
- Activity log
- Pre-defined routine tests

Data Management

- 4 interfaces: USB-A, USB-C, RS232, Ethernet
- Bluetooth option
- Advanced reporting

- Autopublish function
- Drop-to-cursor
- MT-SICS
- EasyDirect Balance software

Sustainable Value

- Full metal housing
- IP43 (10 mg – 100 mg models)
- Overload protection
- Power-saving mode
- Easy-to-clean QuickLock draft shield

Power Consumption

Instrument Steady State	Approx. Power Consumption (W)*
Operational Mode	2.4
Standby Mode	2.2
Power Saving Mode	0.5

*Test results conducted by METTLER TOLEDO under ideal conditions.

Operational Mode = Default balance settings



Applications

- Weighing
- Piece Counting
- Density Determination
- Backweighing
- Formulation
- Check Weighing
- Totaling
- Dynamic Weighing
- Statistics



Accessories

Enhance performance, improve ergonomics, and handle your data efficiently with our wide range of accessories, including EasyDirect Balance data management software, printers, weights, density kit, and Bluetooth adapter.

For further information on accessories, please visit our web page.

► www.mt.com/lab-accessories



Professional Service

With a professional installation, your balance is expertly set up to deliver accurate results from day one.

To learn more about our service offerings, scan the QR code or visit our website:

► www.mt.com/professional-service



DON HO
唐和股份有限公司

台北總公司
台北市內湖區瑞光路618號8樓
02 2627 1088

台中分公司
台中市西屯區朝富路213號22樓-2
04 2252 5037

高雄分公司
高雄市楠梓區德民路220號
07 365 1388

Mettler-Toledo GmbH
Im Langacher 44
8606 Greifensee, Switzerland
www.mt.com/contact

Subject to technical changes.
© 08/2024 METTLER TOLEDO. All rights reserved.
30839978B en
Group Marketing

www.mt.com/MR-precision

For more information



30839978