


XPE Analytical Balances



StaticDetect™ – Sample OK

When static charges are detected, the weighing error is measured. If the user-defined limit is exceeded, a warning is given. For the highest process security, the user can employ anti-static measures to neutralize the charge and ensure the most accurate results.



StatusLight™ – Balance Ready

The StatusLight uses color to indicate intuitively the status of the balance. Green means ready, yellow is a warning and errors are shown with red. The clearly visible light communicates if the balance is ready for you to start your weighing task.



Operation – Ergonomic

The enhanced touchscreen user interface offers tireless, intuitive balance operation. SmartSens sensors allow you to operate your balance with the wave of a hand (e.g. open/close draft shield door). Tasks are easier and safer, and cross-contamination is avoided.



LabX – Processes Under Control

LabX laboratory software provides flexible SOP user guidance on the balance touchscreen. Automatic data handling, calculations and report generation eliminate transcription errors and assure full traceability.

Worry-free Weighing

Follow the Green Light



XPE Analytical Balances

Outstanding Performance

XPE analytical balances provide outstanding performance in analytical weighing and support the highest requirements for safety, efficiency and ease of compliance. Thanks to low repeatability, XPE analytical balances offer you the smallest minimum weight.

Quality management features, such as the innovative StatusLight and patented StaticDetect technology, take the worry out of weighing and provide you with a high level of trust in your results.

With a wide range of accessories available and multiple connectivity options, XPE balances grow with your needs. You can enjoy a wealth of weighing possibilities for years to come.

Designed, engineered and manufactured in Switzerland for outstanding quality you can trust.

METTLER **TOLEDO**

XPE Analytical Balances

Technical Specifications

Limit values	XPE105	XPE205	XPE205DR	XPE204	XPE504
Maximum capacity	120 g	220 g	220 g	220 g	520 g
Readability	0.01 mg	0.01 mg	0.1 mg	0.1 mg	0.1 mg
Readability, fine range	—	—	0.01 mg	—	—
Tare range (from ... to)	0 ... 120 g	0 ... 220 g	0 ... 220 g	0 ... 220 g	0 ... 520 g
Maximum capacity, fine range	—	—	81 g	—	—
Repeatability (nominal) (sd)	0.03 mg (100 g)	0.03 mg (200 g)	0.06 mg (200 g)	0.07 mg (200 g)	0.12 mg (500 g)
Repeatability (5% load) (sd)	0.015 mg	0.015 mg	0.015 mg	0.05 mg	0.08 mg (20 g)
Linearity deviation	0.10 mg	0.10 mg	0.15 mg	0.2 mg	0.4 mg
Eccentricity (test load) ¹	0.12 mg (50 g)	0.2 mg (100 g)	0.25 mg (100 g)	0.25 mg (100 g)	0.4 mg (200 g)
Sensitivity offset (test weight)	0.3 mg (100 g)	0.4 mg (200 g)	0.5 mg (200 g)	0.6 mg (200 g)	1.5 mg (500 g)
Sensitivity temperature drift ²	0.0001%/°C	0.0001%/°C	0.0001%/°C	0.0001%/°C	0.0001%/°C
Sensitivity stability ³	0.0001%/a	0.0001%/a	0.0001%/a	0.0001%/a	0.0001%/a
Typical values					
Repeatability (5% load) (sd)	0.007 mg	0.007 mg	0.007 mg	0.04 mg	0.04 mg (20 g)
Linearity deviation	0.065 mg	0.065 mg	0.1 mg	0.13 mg	0.32 mg
Eccentricity (test load) ¹	0.1 mg (50 g)	0.1 mg (100 g)	0.1 mg (100 g)	0.12 mg (100 g)	0.2 mg (200 g)
Sensitivity offset (test weight)	0.15 mg (100 g)	0.2 mg (200 g)	0.32 mg (200 g)	0.4 mg (200 g)	0.6 mg (500 g)
USP minimum sample weight (5% load, k=2, U=0.1%)	14 mg	14 mg	14 mg	80 mg	80 mg
Minimum sample weight (5% load, k=2, U=1%)	1.4 mg	1.4 mg	1.4 mg	8 mg	8 mg
Settling time	1.5 s	2.5 s	1.5 s	1.5 s	1.5 s
Settling time, fine range	—	—	2.5 s	—	—

¹⁾ according to OIML R76; ²⁾ in the temperature range 10 to 30°C; ³⁾ Stability of sensitivity with proFACT self-adjustment switched on; s: seconds; a: year (annum); sd: standard deviation

Features

Accurate Results	High Resolution Technology Internal Adjustment with Sensitivity Test Internal Temperature Control StaticDetect™
Efficient Operation	Color Touchscreen User Interface in 11 Languages ErgoClips for Direct Dosing Easy Cleaning SmartGrid Hanging Weighing Pan SmartFrac Guided Dosing to Target Automatic Draft Shield SmartSens for Hands-free Operation
Quality Assurance	Graphical Leveling & Level Warning MinWeigh Protection Test Manager FACT, GWP & Admin History 8 Users & Password Protection StatusLight
Seamless Process	Quantos Upgrade Ready LabX Ready RFID Communication Ready Compact Antistatic Kit Ready Built-in RS232 & Optional 2nd Interface

Accessories

	Quantos Upgrade Kit Automated solid and solvent dispensing modules eliminate variability and errors, and offer the highest level of accuracy and safety.		Smart Tag RFID Labels Transfer titration sample information securely from your balance to your titrator via the titration beaker.		EasyScan™ Check testing and calibration dates on RFID tagged pipettes. Record new test dates when you test using the balance application.
	AntiStatic Kits The compact ionizer fixes onto your balance to gently remove charge from the weighing chamber. Free-standing units also available.		Printers The robust P-50 series lab printers produce archival-quality printouts on paper as well as continuous and peel-off labels.		For further information on accessories, please visit www.mt.com/lab-accessories

GWP®

Good Weighing Practice™
www.mt.com/GWP



Mettler-Toledo AG

Laboratory & Weighing Technologies

CH-8606 Greifensee, Switzerland

Tel. +41 44 944 22 11

Fax +41 44 944 30 60

Subject to technical changes

© 01/2014 Mettler-Toledo AG

30094810

Global MarCom Switzerland

www.mt.com/xpe-analytical

For more information